

Miniflow 400 electronic



FLOW-PACKING MACHINE MOD. MINIFLOW 400 ELECTRONIC VERSION.

Loader 160 links (1600 mm) , plates in contact with product : stainless AISI 304.

- Products transport uses shaped porters made of food grade plastic material.
- Film reel holder with locking system and film centring scale.
- Film band : 380 mm
- Film front loading
- Adjustable film forming box (standard).
- 3 Brush-less motors
- 3 Digital drives
- 2 Sets of rollers (1 cold – 1 hot) for feeding and sealing of the film (longitudinal)
- Motorized exit belt.

- Control panel :
 - 7 “ Touch screen display (99 memories for products)
 - Dedicated temperature controllers for longitudinal and transversal sealing.
 - Potentiometer for speed adjustment
 - Emergency STOP button
 - START, STOP, changing rotation button and MAN/AUTO selector.
- Painted in standard RAL 9010-5010

**AVAILABLE IN STAINLESS STEEL CONSTRUCTION :
30 % SURCHARGE**

TECHNICAL DATA

Weight Kg.	300
Installed power (KW)	3
Voltage (Volt)	220 monophase
Package length(mm)	min. 80 - max 400 (1 sealing jaw) min. 70 – max 200 (2 sealing jaws)
Sealers length (mm)	160
Film width (mm)	380
Max bag width (mm)	160
Product height max(mm)	60 (80 with modified jaw shaft : optional)
Overall dimensions (mm)	2300 x 800 x 1800
Wrapping speed*	Max. 120 cycles/min

*Depends on product dimension and/or configuration (1 or 2 sealing jaws)

Adjustable film conformer

included

Photocell for centered printing

included